

LASYSTEMS - Brusselsesteenweg 208 - 1730 Asse - Belgium

Phone: +32-2-4531312 - Fax: +32-2-4531763 E-mail: info@lasystems.be

## Sharp PG-D2500X (PG-D2500X)

PGD2500X - DLP XGA 1024 x 768, 3D Ready, 2500 ANSI Lumen, 2.8kg



Price details: Price excl. VAT:  $565.29 \in$ Eco fees:  $0.29 \in$ VAT 21 %: 118.77  $\in$ Product details: Product code: PG-D2500X EAN: 4974019656786 Manufacturer: Sharp  $684.35 \in$  PDF generated on: 24 September, 2012



Product is discontinued. You can not order it anymore.

\* VAT included

New Sharp 3D ready Projector with BrilliantColour Technology and six segment colour wheel dramatically improves image quality

- 3D ready projector incorporating DLP link Technology

- Rich and vibrant colour reproduction with BrilliantColour technology and six-segment colour wheel (RGBWCY)
- 2,500 ANSI lumens brightness
- High resolution images up to UXGA (1,600 x 1,200) and SXGA+ (1,400 x 1,050) compatibile in Intelligent
- Compression System
- Direct power off and quick start
- Compact size with filter free design and sliding lens cover
- Remote control with GUI pointer and spotlight
- 4:3 native aspect ratio with 16:9 compatibility and image shift function
- Long lamp life up to 4000 hours (eco+quite mode)

Main specifications:

Projector Projector brightness: Projection technology: Native resolution: Screen size compatibility: Projection distance: Aspect ratio: Contrast ratio (typical): Throw ratio: Zoom ratio: Resolution:	2500 ANSI lumens DLP XGA (1024x768) 40 - 300 " 1.4 - 12.6 m 4:3 1100:1 1:1.7 - 2.1 1:1.2 1600 x 1200 pixels
Lens system Focus: Focal length: Lens focal range: F-number (relative aperture):	Manual 19 - 22.7 mm 2.4 - 2.6 2.4 – 2.6
Scanning frequency Vertical scan range: Horizontal scan range: Dot clock scanning frequency:	45 - 85 Hz 15 - 110 kHz 165 MHz
Lamps Service life of lamp: Lamp power:	2000 h 210 W

Service life of lamp (economic mode):	4000 h
Connectivity DVI port: Component video (YPbPr/YCbCr) in: HDMI ports quantity: USB 2.0 ports quantity: Composite video in: Audio (L,R) in: S-Video in: Ethernet LAN (RJ-45) ports quantity: RS-232 ports: VGA (D-Sub) ports quantity: Speaker/ headphone/ line-out jack:	N 3 0 1 - 1 1 N 1 2 1
Video Analog signal format system:	NTSC 3.58, 4.43 / PAL, 60, M, N / SECAM
Audio Built-in speakers: Number of built-in speakers: RMS rated power:	Y 1 7 W
Networking Ethernet LAN connection: Wireless LAN (WLAN) connection:	N N
Energy management Power consumption: Battery technology: Battery type: Power consumption (standby):	274 W Alkaline AA 0.32 W
TV tuner TV tuner integrated:	Ν
Weight & dimensions Dimensions (WxDxH): Weight:	300 x 236 x 79 mm 2812 g
Storage media Card reader integrated:	Ν
Technical details Handheld remote control: Connectivity technology: Power requirements: Size: Ceiling mountable: Video compatibility mode:	Y Wireless 100–240 V AC, 50/60 Hz 0.7 " Y UXGA, SXGA, SXGA+, WXGA, XGA, SVGA, VGA
Security Cable lock slot:	Kensington