# EB-X25

The EB-X25 is our latest LCD projector that features an XGA resolution, 1.2x optical zoom and equally high White and Colour Light Output of 3,500 lumens. This offers small businesses and classrooms colours that are three times brighter<sup>1</sup> than 1-chip DLP projectors.

**EPSON** 

# High quality, bright and vibrant images

This LCD projector effortlessly displays bright images with vivid colours for a crisp, clear picture: ideal for presentations and moving images, and is aided by the 10,000:1 contrast ratio. With an HDMI input, high definition video and audio content are easily played with the same high quality you would expect from the world's number one projector manufacturer<sup>2</sup>.

# Ethernet projector

The Ethernet connectivity allows you to control and monitor the projector and display your content across a LAN network.

### More control and collaboration

With the moderator function, you can easily allow others to connect and share their content over your LAN. You remain in complete control and can choose when to display content – ideal for interaction in a collaborative teaching or training environment.

# User-friendly

Thanks to its manual keystone slider – unique to Epson – and automatic vertical keystone correction, this projector is quick and simple to set up. No matter the angle of the projector, you can easily align the projection to ensure a straight and correct image. The Colour Universal Design makes operating the projector easier, thanks to new LED colours and menu icons on the projector's control panel.

# **KEY FEATURES**

3LCD HƏMI

> • Exceptional value No quality compromise, on a budget

✓ ✓ × ×

- Very bright output 3,500 lumens White Light Output and 3,500 lumens Colour Light Output
- Sharp detail 10,000:1 contrast ratio
- Easy set-up Automatic vertical keystone correction
- Ethernet Connectivity Control, monitor and display content over a LAN





# PRODUCT SPECIFICATIONS

| IMAGE                        |  |
|------------------------------|--|
| Colour Reproduction          | Upto 1.07 billion colours  |
| Colour Light Output          | 3.500 lumen-2.450 lumen (economy)  |
| White Light Output           | 3.500 lumen - 2.450 lumen (economy) In accordance with ISO 21118:2012                          |
| Resolution                   | XGA, 1024 x 768, 4:3   |
| Contrast Ratio               | 10.000 : 1   |
| Lamp                         | 200 W, 5.000 h durability, 6.000 h durability (economy mode)                                   |
| Keystone Correction          | Auto vertical: ± 30 °, Manual horizontal ± 30 °  |
| TECHNOLOGY                   |  |
| Projection System            | 3LCD Technology  |
| LCD Panel                    | 0,63 inch with MLA (D7)  |
| OPTICAL                      |  |
| Projection Ratio             | 1,40 - 1,68:1  |
| Zoom                         | Manual, Factor: 1,2  |
| Projection Size              | 30 inches - 300 inches   |
| Projection Distance Wide/Tel | e 1,71 m - 2,16 m (60 inch screen)   |
| Projection Lens F Number     | 1,6 - 1,74   |
| Focal Distance               | 18,4 mm - 22,08 mm   |
| Focus                        | Manual   |
| Offset                       | 8,6 : 1  |
| CONNECTIVITY                 |  |
| USB Display Function         | 3 in 1: Image / Mouse / Sound  |
| Interfaces                   | USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), VGA in (2x), VGA out,   |
|                              | HDMI in, Composite in, Component in (2x), S-Video in, RGB in (2x), Stereo mini jack audio out, |
|                              | Stereo mini jack audio in (2x), Cinch audio in   |
| Epson iProjection App        | Ad-Hoc / Infrastructure  |
| ADVANCED FEATURES            |  |
| Security                     | Kensington lock, Password lock, Security cable hole  |
| Features                     | AV Mute Slide, Built-in speaker, Direct Power on/off, Document Camera Compatible,              |
|                              | Horizontal and vertical keystone correction, Network administration, Network projection        |
| Video Colour Modes           | Blackboard, Dynamic, Presentation, Sports, sRGB, Theatre, Whiteboard                           |
| GENERAL                      |  |
| Energy Use                   | 270 W, 223 W (economy), 0,47 W (standby)   |
| Product dimensions           | 297 x 244 x 87 mm (Width x Depth x Height)   |
| Product weight               | 2,6 kg   |
| Noise Level                  | Normal: 37 dB (A) - Economy: 29 dB (A)   |
| Included Software            | EasyMP Monitor, EasyMP Multi PC Projection, EasyMP Network Projection                          |
| Loudspeaker                  | 5 W  |
| OTHER                        |  |
| Warranty                     | 24 months Carry in, Lamp: 12 months or 1.000 h   |

# LOGISTICS INFORMATION

| SKU                      | V11H575040                 |
|--------------------------|----------------------------|
| EAN code                 | 8715946532554              |
| Dimensions Single Carton | 363 x 397 x 160 mm         |
| Carton Weight            | 4,12 Kg                    |
| Country of Origin        | Multiple country of origin |
| Pallet Size Euro         | 78 Units (6 x 13)          |



1. 1Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour Brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour Brightness will vary depending on usage conditions. For more information please visit www.epson.eu/CLO 2Survey conducted by Futuresource Consulting Limited for the period from 2001 to 2012.



### **EB-X25**

### WHAT'S IN THE BOX

- Carrying bag
- Computer cable
- Main unit
- Power cable
- Remote control incl. batteries
- User's Manual Set
- Warranty Documents

### **OPTIONAL ACCESSORIES**

- Air Filter ELPAF32 EB-SXW11/12/14 V13H134A32
- Ceiling Mount ELPMB23 White V12H003B23
- Ceiling pipe ELPFP13 668-918mm V12H003P13
- Ceiling pipe ELPFP14 918-1168mm V12H003P14
- Lamp ELPLP78 EB-SXW03/SXW18/X24 V13H010L78
- Screen ELPSC24 80" Pantograph 16:10 V12H002S24
- Screen ELPSC26 80" Multi-Aspect V12H002S26
- Screen ELPSC32 50" Desktop type V12H002S32